

RX eco FORCE

380e - 450e - 500e

Ultra strong two motor carpet cleaner for large areas

STRENGTHS

- › Selected by the White House U.S.A.
- › Strong and reliable - ideal for contract cleaners
- › 5 levels of filtration with HEPA filter (optional)
- › Accessories on board
- › Double body/base support with quick release
- › Stainless steel guides anti wear
- › Available in 3 sizes: 380 (15"), 450 (18", 500 (20")
- › Energy consumption combined: class "B"



eco FORCE



TECHNICAL DATA

	RX eF 380e	RX eF 450e	RX eF 500e
Input power (W)	880	900	900
Water lift mm/H ₂ O (in/ H ₂ O)	2300 (90)	2300 (90)	2300 (90)
Air volume lt/sec (CFM)	49 (103.8)	49 (103.8)	49 (103.8)
Motor protection	Termo/amp.	Termo/amp.	Termo/amp.
Two ply paper bag (lt.)	4	4	4
Washable TNT bag and Micropore	Optional	Optional	Optional
Exhaust Microfilter 3M Filtrete	Standard	Standard	Standard
Hepa filter H11	Optional	Optional	Optional
Cogged drive belt	Standard	Standard	Standard
Electronic overload/speed control	Standard	Standard	Standard
Center convergent bristles brush (RPM)	5000	4500	4500
Anti wear shoe plate	Stainless steel	Stainless steel	Stainless steel
Working capacity m ³ /H (sq. ft./H)	630 (6700)	750 (8000)	850 (9100)
Sound power (db)	79	79	79
Total weight Kg (lb)	7,79 (17.2)	8,16 (17.9)	8,25 (18.2)
Cord lenght mt. (ft.)	10 (41)	10 (41)	10 (41)
Energy consumption combined (Class)	B	B	B

1. Electronic control provides for a soft start, overload indication for the correct height adjustment and motor shut off.
2. The dynamically balanced roller and metal supports with ball bearings can be quickly replaced without tools. The RX is equipped with 4 rubber wheels as well as two side cylinders to glide flush with the wall. Two wear resistant stainless steel base guides provide a shockproof system. Two position operation provides easy transition over thresholds.
3. Air and dust are highly filtered and special attention was given to the power nozzle with a washable entry/exit cooling air filter – easily replaced without tools.
4. Thanks to the stretch hose and the telescopic wand on board, is possible to connect the M28R hard floor tool.

